

«PeakTech® P 2005 A» 1000 V digital multimeter 2000 Counts, 10A AC/DC



€39.90

Prices excl. VAT plus shipping costs and possibly lower value surcharge

Product number: P 2005 A

GTIN/EAN: 4250569405587

## Description

---

The new PeakTech 2005 A offers a multitude of measurement functions for electrical measured variables for every user from industry, craftsmanship, training, hobby and the laboratory. It was manufactured according to the latest development aspects and has a double-insulated injection-molded housing with rubber coating, a tilt stand on the back, which can be removed to replace the batteries. The fuses are located underneath the stand as well, if it is necessary to replace these. The device is working with a battery and has an LCD screen with a character height of 32 mm. The manual range selection enables a very fast response time and the measured values can be easily read on the illuminated display. The PeakTech 2005 A can be used to measure DCV, ACV, DCA, ACA, resistance, capacitance, diode, transistor, continuity, temperature, frequency and inductance, which create a wide range of applications. Due to the high overvoltage category CAT III 1000V, you can use this device safely on electrical installations and systems.

## Technical features

---

- 32 mm, 3 1/2 digit LCD display (max. 1999) with backlight
- Manual range selection with fast response time
- Inductance measurement up to 20 H
- HFE transistor-test
- PeakHold function

PeakTech Prüf- und Messtechnik GmbH  
Gerstenstieg 4  
DE-22926 Ahrensburg  
[www.peaktech.de](http://www.peaktech.de)

- Temperature measurement using type-K probe
- Auto power off and low battery indication
- Safety: EN 61010-1; CAT III 1000 V
- Accessories: Carrying case, test leads, thermocouple, temperature adapter, battery and user manual

## Specifications

---

**Basic Accuracy DC:** +/- 0,5%

**Capacitance max.:** 200 µF

**Digital counts:** 2.000

**Display Type:** LCD

**Inductance max.:** 20 H

**Over voltage category:** CAT III 1000 V, CAT IV 600 V

**Range selection:** Manual

**True RMS:**

**V DC max.:** 1000V

**hFE:**

**A AC max.:** 10A

**Hz max.:** 10 MHz

**OHM max.:** 2000 MΩ

**Temp. max.:** 1000 °C

**Temp. min.:** -20 °C

**mA DC max.:** 200mA

**V AC max.:** 1000V

**A DC max.:** 10A

**mA AC max.:** 200 mA