

«PeakTech® P 1370» 60 MHz / 4 CH, 1 GS/s touchscreen oscilloscope



€999.90

Prices excl. VAT plus shipping costs and possibly lower value surcharge

Product number: P 1370

GTIN/EAN: 4250569404429

Description

The PeakTech 1370 is a 60 MHz 4-channel digital storage oscilloscope of the latest generation with a high-resolution TFT touchscreen and extensive additional functions. It has a sampling rate of up to 1 GS / s and impresses with its high quality and easy handling with the best price / performance ratio. Of course, all models in this series have an XY mode and an FFT function as well as an integrated frequency counter. With its integrated 4000 counts multimeter for voltage, current and resistance measurements, this device can be used as a mobile workplace in the laboratory, service and industry. The integrated decoders for CAN bus, RS-232, I2C and SPI enable an analysis of bus signals and the display of an event table. The data is transferred to the PC via a LAN connection or the USB interface, whereby waveforms can also be saved on a USB memory stick while on the move.

Technical features

- 4-channel oscilloscope with 60 MHz analog bandwidth at max. 1 GS/s sampling rate
- 20 cm (8 ") TFT touchscreen for user-friendly operation
- Integrated digital multimeter with 4000 counts
- WiFi, LAN and USB device connection for real-time data transmission
- USB host connection for external USB data carriers
- CAN bus, RS-232, I2C, SPI decoder with event table
 Gerstenstieg 4
- Autoset function for user-friendly operation DE-22926 Ahrensburg

www.peaktech.de



- Recording length of max. 40 million points
- Optional battery: "Akku 6" model
- Safety: EN 61010-1; CAT II 400 V
- Accessories: USB cable, software CD for Windows, power cord, 2 probes, BNC cable, carrying case and manual

Specifications

Sampling 1 CH: 1 GS/s

Sampling 2 CH: 500 MS/s

Sampling 4 CH: 250 MS/s

USB:

Bandwidth: 60 MHz

Battery: Li-Po 13200 mAh (optional)

Channels: 4 CH

Display Type: Touchscreen TFT

Hor. scale max.: 1000 s/div

Hor. scale min.: 1 ns/div

LAN:

Mains voltage: 110/240 V AC; 50/60 Hz

Memory depth: 40.000.000 Points

Resolution: 800 x 600 Pixel

Rise Time: < 5.8 ns

Screen size (TFT): 20 cm (8")

VGA:

Vert. resolution: 8 Bit

Vert. scale max.: 10 V/div

Vert. scale min.: 1 mV/div

Integr. AWG:

Integr. DMM: