

«PeakTech® P 1625» TrueRMS clamp meter 4,000 counts 1000 A AC/DC



€129.90

Prices excl. VAT plus shipping costs and possibly lower value surcharge

Product number: P 1625

GTIN/EAN: 4250569400322

Description

The PeakTech 1625 is a measuring device for AC and DC currents up to 1000 A using a current clamp for conductor diameters up to 35mm. Current and voltage measurements are carried out as True RMS (true rms value) measurements, which means that the measured values ~~are~~ are displayed correctly even with waveforms that deviate from a sine wave. Current clamps are ideal for current measurement in electrical systems and control cabinets, since only single wires are guided through the clamp jaws for contact-free current measurement and no electrical connections have to be disconnected. In addition, this model has extensive multimeter functions for voltage, resistance, frequency, capacitance and temperature measurement. Continuity tests with acoustic signals and diode tests can also be carried out. Due to its high functionality and simple handling, this current clamp is suitable for electronics specialists, service technicians or hobbyists.

Technical features

- True RMS AC alternating current and DC direct current measurements up to 1000 A.
- LCD display with 4000 digits, bar graph and backlight
- True RMS voltage measurements up to 600 V AC / DC
- Resistance measurement, continuity tester and diode test
- Frequency measurement and Hz / duty function
- Capacitance measurement function up to 40 mF

PeakTech Prüf- und Messtechnik GmbH
Gerstenstieg 4
DE-22926 Ahrensburg

www.peaktech.de

- Temperature measuring function with enclosed sensor
- Data hold function, automatic and manual range selection
- Zero function for direct current measurements
- Conductor diameter up to max. 35 mm
- Safety: TÜV / GS, EN 61010-1, CAT III 600 V
- Accessories: temperature sensor and adapter, carrying case, test leads, battery and manual

Specifications

Capacitance max.: 40 mF

Clamp Opening: 35 mm

Digital counts: 4.000

Display Type: LCD

GS - Tested safety:

Over voltage category: CAT III 600 V

V DC max.: 600V

A AC max.: 1000 A

Hz max.: 4 kHz

OHM max.: 40 MΩ

Temp. max.: 1000 °C

Temp. min.: -40 °C

mV DC max.: 400 mV

V AC max.: 600 V

mV AC max.: 400 mV

A DC max.: 1000A