

«PeakTech® P 1885» Laboratory power supply DC 1 - 40V / 0 - 5A with USB



€369.90

Prices excl. VAT plus shipping costs and possibly lower value surcharge

Product number: P 1885

GTIN/EAN: 4250569400384

Description

The PeakTech 1885 is a programmable laboratory power supply for a maximum of 40V / 5A DC, i.e. 200 W continuous power. In addition to presets for current and voltage values, time programs with intervals and the number of runs can also be created directly on the device or using the included PC software. For operation with a PC, the switching power supply is equipped with a USB and RS-485 interface. A PC connected to the RS-485 interface enables the control of up to 32 power supplies. A USB interface on the back of the device connects to a Windows PC. The intelligent fan control adjusts the speed of rotation to the respective temperature and output power. The output voltage and current limit can also be set in the open circuit without a connected load. Due to its high reliability and the programming functions, this power supply series is ideal for professional users from industry, control and regulation technology or the electronics laboratory.

Technical features

- DC laboratory switching power supply with max. 40 V / 5 A
- Multi-line LCD display with backlight
- 4 mm safety sockets for connecting a consumer
- USB and RS-485 interface for connection to the PC
- Freely adjustable presets for current and voltage values
- Freely adjustable time programs and cycle times

PeakTech Prüf- und Messtechnik GmbH
Gerstenstieg 4
DE-22926 Ahrensburg

www.peaktech.de

- Display of setpoint and real value for voltage and current
- Watt display for current output power
- Short circuit; Overload and overtemperature protection
- Safety: EN 61010-1
- Accessories: USB cable, RS-485 connector, software CD for Windows, power cord and manual

Specifications

USB:

Channels: 1 CH

Display Type: LCD

Input connector: IEC socket

Input voltage: 100 - 240 VAC 50/60 Hz

Output Connection: 4 mm Buchse

Output Current: 0 - 5 A

Output Voltage: 1 - 40 V DC

RS-485: